

JUN 26 2008

Request for Reconsideration After Non-Final Rejection
Serial No. 10/776,718

Docket 5000-1-513

IN THE CLAIMS:

There are no amendments at this time. A clean copy of the claims has been provided herein below as a courtesy.

1. (Previously Presented) An automatic gain control (AGC) apparatus having a short settling time in a burst mode optical receiver, comprising:

a variable gain amplifier for variably amplifying an input signal according to an AGC adjustment control signal;

a clipper coupled to an output terminal of the variable gain amplifier for comparing an output signal of the variable gain amplifier with a preset signal V_{cut} and for outputting a signal difference only when the output signal of the variable gain amplifier is higher than or equal to the preset signal V_{cut} in amplitude, and wherein said clipper clips the output signal of the variable gain amplifier only when the output signal is lower than said preset signal V_{cut} ;

an exponential amplifier for exponentially amplifying an output signal of the clipper; and

a peak holder for detecting a peak value from an output signal of the exponential amplifier and for generating the AGC adjustment control signal for controlling a gain of the variable gain amplifier.

2. (Original) The AGC apparatus of claim 1, further comprising a voltage controlled variable resistor (VCVR) coupled in parallel to the peak holder for creating a

Request for Reconsideration After Non-Final Rejection
Serial No. 10/776,718

Docket 5000-1-513

current leakage path and for preventing overcurrent from flowing in the peak holder when the output signal of the exponential amplifier is larger than or equal to a preset threshold.

3. (Original) The AGC apparatus of claim 1, wherein the peak holder comprises:

a peak value detector for converting a DC (Direct Current) level of an output signal of the exponential amplifier so that the DC level of the output signal of the exponential amplifier is matched to a DC level of the peak holder; and

a peak value keeper for keeping a peak value of the output signal of the exponential amplifier and for generating the AGC adjustment control signal to control a gain of the variable gain amplifier from the kept peak value.

4. (Previously Presented) An automatic gain control (AGC) apparatus having a short settling time in a burst mode optical receiver, comprising:

a variable gain amplifier for variably amplifying an input signal according to an AGC adjustment control signal;

a clipper coupled to an output terminal of the variable gain amplifier for comparing an output signal of the variable gain amplifier with a preset signal V_{cut} and for outputting a signal difference when the output signal of the variable gain amplifier is higher than or equal to the preset signal V_{cut} in amplitude, and wherein said clipper clips

Request for Reconsideration After Non-Final Rejection
Serial No. 10/776,718

Docket 5000-1-513

the output signal of the variable gain amplifier when the output signal is lower than said preset signal V_{cut} ;

an exponential amplifier for exponentially amplifying an output signal of the clipper; and

a peak holder for detecting a peak value from an output signal of the exponential amplifier and for generating the AGC adjustment control signal for controlling a gain of the variable gain amplifier,

wherein the peak holder comprises:

a peak value detector for converting a DC (Direct Current) level of an output signal of the exponential amplifier so that the DC level of the output signal of the exponential amplifier is matched to a DC level of the peak holder; and

a peak value keeper for keeping a peak value of the output signal of the exponential amplifier and for generating the AGC adjustment control signal to control a gain of the variable gain amplifier from the kept peak value,

wherein the peak value keeper initializes the kept peak value according to an initialization signal.

5. (Original) The AGC apparatus of claim 4, wherein, upon receiving a signal that there is no more data input to the AGC apparatus, the initialization signal is delivered to initialize the peak value keeper in order to detect a new peak value when the next data is received.

Request for Reconsideration After Non-Final Rejection
Serial No. 10/776,718

Docket 5000-1-513

6. (Previously Presented) An automatic gain control (AGC) apparatus having a short settling time in a burst mode optical receiver, comprising:
- a variable gain amplifier for variably amplifying an input signal according to an AGC adjustment control signal;
 - a clipper coupled to an output terminal of the variable gain amplifier for comparing an output signal of the variable gain amplifier with a preset signal V_{cut} and for outputting a signal difference when the output signal of the variable gain amplifier is higher than or equal to the preset signal V_{cut} in amplitude, and wherein said clipper clips the output signal of the variable gain amplifier when the output signal is lower than said preset signal V_{cut} ;
 - an exponential amplifier for exponentially amplifying an output signal of the clipper; and
 - a peak holder for detecting a peak value from an output signal of the exponential amplifier and for generating the AGC adjustment control signal for controlling a gain of the variable gain amplifier,
- wherein the clipper and the exponential amplifier comprise:
- a first transistor having a base receiving an output signal of the variable gain amplifier, a collector connected in common to a supply voltage V_{cc} on one end of a first resistor, and an emitter connected in common to an emitter of a second transistor and one end of a second resistor;
 - a second transistor having a base receiving a specific voltage value corresponding to a preset clipping value, a collector connected to another end of the first resistor, and an

Request for Reconsideration After Non-Final Rejection
Serial No. 10/776,718

Docket 5000-1-513

emitter connected in common to the emitter of the first transistor and one end of the second resistor;

the first resistor having one end connected in common to the collector of the first transistor and the supply voltage V_{cc} , and another end connected to the collector of the second transistor; and

the second resistor having one end connected in common to the emitter of the first transistor and the emitter of the second transistor, and another end grounded.